

A001B : SELDUR BLACK

black pigmented metallised polish



Description of product

A metallised polish for extreme strength and durability coupled with ease of removability. Produces a deep shine with excellent slip resistance. Responds brilliantly to all spray burnishing techniques. For all linoleum, P.V.C., rubber, sealed cork, sealed wood, terrazzo and thermoplastic floors. N.B. Not suitable for unsealed wood, unsealed cork or laminate flooring.

Product Uses


To enhance and protect black asphalt, rubber and sealed floors.

Directions

DIRECTIONS: Seldur Black must be applied to a clean grease free floor. Strip old polish with Selate then rinse thoroughly with clean water, allow floor to dry. Apply a thin even film of Seldur Black using a clean lint free mop or applicator. Apply a second coat when the first is dry (approximately 30 minutes). May be buffed as required to enhance gloss. COVERAGE: 60 square metres per litre.

iNsignt Supported

iNsignt is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>



iNsignt recommended product uses

Flooring - applying floor polish (mop application)

typical dilution
neat

Product Hazards and PPE Requirements

Contains : Benzothiazolinone

Risk Phrases
Contains Benzothiazolinone May produce an allergic reaction.

Safety Phrases

Technical Data

Composition A blend of acrylic copolymers, resins and copolymer wax incorporating wetting agents and film forming aids in a stable water based emulsion form incorporating metal cross linking additives.

Appearance Translucent emulsion

Colour Pigmented black

Viscosity <10 cps

Density 1.025

pH 8.0 - 8.2

Activity 18%

Fragrance Characteristic, slightly sweet

Stability 2 years in unopened container

Storage Protect from freezing

Environmental Profile

Biodegradability
All surfactants contained in Selden Products meet the requirements of the EU Detergent Directive 2005 – 2004/648/EC. This requires all surfactants to break down both quickly and completely into harmless material such as CO2 and water.

Selden Environmental Charter


- We set ourselves industry leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.

Visit our website for more information.

External Accreditations


- 9001 - Quality System
- 14001 - Environmental System
- 18001 - Health & Safety System
- IPPC Certified Manufacturer

Sustainability
Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

- english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



UKAS
accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

