

K033 : MAINTENANCE SPRAY



Description of product

A blend of penetrating solvents, water dispersing agents and corrosion inhibitors. Instantly displaces all water from damp or wet components. Penetrates deeply to prevent moisture traps. Leaves a protective film to waterproof and guard against corrosion. Lubricates - increases efficiency of working parts.

Product Uses


Pre-spray electrical connections to prevent short circuiting due to water. Can even be used on damp connections to displace problem causing moisture. Penetrates and helps free seized threads and bearings. Protects against further corrosion. Cleans grime from threads and components.

Directions

For cleaning applications either spray directly onto surface and allow to penetrate and then wipe off, or for more difficult areas use extension tube and a more directional spray to force away grime . N.B. Do not spray on short circuits where sparking is likely.

iNsight Supported

iNsight is Selden's interactive product selection and training system. Enables the user to create full COSHH training kits, wallcharts, task cards and more. visit <http://www.selden.co.uk/insight>




iNsight recommended product uses
Special - maintenance aerosols (lubrication/cleaning)

typical dilution n/a

Product Hazards and PPE Requirements

Danger



Contains : Calcium sulfonate

Risk Phrases
Contains Calcium sulfonate. May produce an allergic reaction. Extremely flammable aerosol. Causes serious eye irritation. Pressurised container: May burst if heated.

Safety Phrases
Keep out of reach of children. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear eye protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

Technical Data

Composition	Penetrating solvents, lubricants, dewatering agents and rust preventives
Appearance	Clear spray
Colour	Pale amber
Density	0.67
Fragrance	Sweet characteristic
Stability	Two years minimum
Storage	Pressurised container. Store out of direct sunlight. Temperature must not exceed 50°C

Aerosol Information

Propellant	Hydrocarbon
Pressure	56 psi
Spray Rate	1.6

Environmental Profile

Biodegradability

Selden Environmental Charter

- We set ourselves industry leading standards.
- Selden minimises wastage, packaging and transportation.
- If it can be recycled, it will be recycled.
- Our chemicals policy exceeds regulatory requirements.
- We don't expect other people to clean up after us.
- Conserving energy, preserving resources.
- By being innovative, we strive to do better.
- We like to work in partnership with our clients.


Visit our website for more information.

External Accreditations

- 9001 - Quality System
- 14001 - Environmental System
- 18001 - Health & Safety System
- IPPC Certified Manufacturer

Sustainability

Product conforms with the DEFRA endorsed Sustainable Cleaning guidance



COSHH+ Supported

Selden's bespoke COSHH awareness and product training tool. Users specify the products in use and instantly generate a full training pack to enable quick and effective staff training.



www.flagship-mcp.com

Flagship products are those products that are included in Selden Multi-language Cleaning Programme. Flagship products have induction kits, best practise guidance, MSDS, wallcharts and usage guides available in the following languages

- english, french, spanish, portuguese, polish, german, dutch, russian, romanian, estonian, czech, croatian.



UKAS
accredited testing
laboratory No. 4204



SELDEN
formulating
testing
manufacturing
to
the highest
standards

Selden Research Limited

Staden Business Park, Staden Lane, Buxton Derbyshire. SK17 9RZ

Tel : 01298 26226 | Fax : 01298 26540 | Email : info@selden.co.uk | web : www.selden.co.uk

