





#### The development of floors and flooring materials within the broad range of commercial developments has been very pronounced over the past decade.

Not only have floors become more exotic in both design and material selection but, equally, we all expect to see the floor maintained to an exceptionally high standard, literally sparkling cleaning, in high profile locations; super clean in the workplace and public space... just as we would expect in our own living space.

#### Contents

Hurricane NuSpeed TwinTec Mains / Cable TwinTec Battery

### Thermoplastic The Right Equipment For The Right Job Will Provide The Right Results.

4-7	TwinTec Vario	20-21
8-9	TwinTec Ride-on	22-27
10-13	Brushes and Pads	28-29
14-19	Accessories	30-31



# Hurricane The 1000W Size

#### The single disc floor machine is the heart of all hard floor cleaning and maintenance.

The Hurricane motor concept is designed to keep its "Cool" under continuous and arduous operation whilst its seamless power transmission to the floor is via our longlife, oil filled, low load planetary gearbox. THE HFM1015 150rpm machine is equipped with the 1000W Hurricane motor providing a lighter weight and economical solution.

- Planetary Gearbox Longlife, oil filled, low load planetary gearbox.
- Hi-Cool Motor Heavy duty, long life motor.
- **ATC** (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.
- Fully Adjustable Handle For the perfect working position.


NuLoc2 Pad Drive System option


Large solution tank optio

All Hurricane models incorporate our ATC, Automatic Torque Control, monitoring and balancing operational power input throughout the cleaning cycle.



Optional Hi-Dust Motor Filter





HFM1015



### The HFM1500 series is available in a choice of 4 different speeds, 150rpm, 230rpm, 300rpm and extra Hi-speed 450rpm.

All models are fitted as standard with our generous oversize Hurricane 1500W drive motor allowing for higher speeds and the use of added weight as required.

The longlife, low load, oil filled planetary gearbox ensures seamless power transmission to the floor ensuring excellent results.

With the range of speeds available machines can be selected to cover the whole range of floor care maintenance be it scrubbing, polishing, buffing, burnishing or spray cleaning.

- Planetary Gearbox Longlife, oil filled, low load planetary gearbox.
- NuLoc2 Systems Optional pad interchange systems, quick, simple and secure.
- Hi-Cool Motor 1500W motor allowing for higher speeds and the use of added weight as required. Available in a choice of 4 speeds 150rpm, 230rpm, 300rpm, 450rpm.
- **ATC** (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.
- Fully Adjustable Handle Adjustable for the perfect position.

 Accessories A range of accessories available to cover wet applications, carpet shampooing, vacuum polishing and floor sanding.



HFM1515 HFM1523 1500W 450mm HFM1530 HFM1545

Optional 10kg additional weight

4 (See page 30 for full accessories) Images may include optional access





HFM1515



Optional spray clean system

Brush	Pad	Power	Speed	Vacuum	Range	Weight	Dimensions (WxLxH)
			150rpm				
450	100	230V AC 50Hz	230rpm	Optional	~~	32kg	
450mm	400mm		300rpm		32m		460x560x1250mm
			450rpm				

# Hurricane The Two Speed

### There are more and more applications where the floor machine must fulfil two functions literally at the "Flick of a Switch".

The HFT model is fitted with the Hurricane dual performance motor rated at 1000W / 1250W providing optimised power options at the two different operating speeds. For scrubbing you want 150rpm but for polishing 300rpm giving quicker and better results. This is very much the case in hospitals, care homes, hotels, schools, etc. where the needs vary quite substantially each day and two separate machines are not always practical or available.



- Planetary Gearbox Longlife, oil filled, low load planetary gearbox.
- Dual Speed

Dual speed motor giving speeds of 150rpm for scrubbing and 300rpm for polishing.

 ATC (Automatic Torque Control) Monitoring and balancing power input throughout the cleaning cycle.


Accessories A range of accessories available to cover wet applications, carpet shampooing, vacuum polishing and floor sanding.



Adjustable handle

ptional 10kg Additional weight (150rpm

HFT1530



6 (See page 30 for full accessories) Images may include optional accessories for ill



# Humicane NUShine The High Speed Burnisher

#### Great styling, easy control and powerful. Designed to allow for effortless performance at higher burnishing speeds. When size and weight are a factor the HNS offers the ideal balance.

A compact yet powerful machine with supreme manoeuvrability. If you want stunning results combined with effortless performance then this is the machine for you. The NuShine has complete directional control which means a consistently high standard of finish.

- Powerful Hi-Cool 1500W Motor Heavy duty, longlife motor.
- Automatic Torque Control Monitoring power and balance.
- Fully Adjustable Operator Handle Easy to use and fully adjustable operator handle.
- Effortless All direction control with superb manoeuvrability.
- Brush Pressure Monitor Allowing you to be in control of the surface finish achieving optimum results with superior handling.



Simple load adjustment





Hurricane Hi-Cool heavy duty

500mm

HNS1550

alla.

1500W

Speed Pad Pressure Cleaning Range Weight 32m 25kg

# **NuSpeed** The Super Compact Size

### The LoLine will put truly usable power, convenience and efficiency in the hands of the operator, giving superb results.

The LoLine rotary has been designed specifically to meet the demand and raise the handling and performance levels to an exceptional user friendly standard.

Our LoLine NLL332 can claim performance characteristics equal to that of bigger, more industrial machines, yet with an ease and speed of operation that will immediately endear it to any user.


A full range of 33cm (13") brushes and pad drives allows the machine to be used for all of the primary floor care functions.





• **Pads and Brushes** Full range of 33cm (13") brushes and pad drives for all primary floor care functions.

- Easy Storage Only 18kg in weight, compact size and folding design means easy and convenient to move and store.
- 200rpm 200rpm means versatility but equals performance of bigger more industrial machines





Model Motor Deck Brush Pad Power Speed Vacuum Range Weight Dimensions (WxLxH) NLL332 400W 330mm 330mm 330mm 230V AC 50/60Hz 200rpm -32m 18kg 450x580x1185mm

# **NuSpeed** The Full Size

#### The NuSpeed range of professional FloorCare machines has been specifically designed to provide optimum results whatever the application.

All NuSpeed NR models within the range are equipped with our performance enhancing ATC (Automatic Torque Control) feature. This is a unique system that monitors operation and boosts torque as required to provide consistent performance under varying load conditions.


#### • ATC

ATC (automatic torque control) monitoring and balancing power input throughout the cleaning cycle.

Xtra Weight

Unique NuSpeed design means an increase in operating weight of 40kg can be achieved within the standard specification.

 Easy Storage Compact size and folding handle means easy and convenient to move and store.



Model Deck



NR1500 folded for storage



IATA

L MEAN THE ME WALLAND CHAINE AND SOLVENSY

# TwinTec The Cylinder Machine

#### Designed to be compact, easy to operate and exceptionally manoeuvrable when in use, whilst the oversized transit wheels allow easy movement to and from any specific locations.

The cylinder power brush ensures deep cleaning performance, whilst the twin water pick-up nozzles allow multi-directional operation which is vitally important when cleaning narrow walkways often found in shops and food stores. You can walk in forwards and reverse out without turning and without loss of scrubbing and drying performance.



Please note: Available January 2017

Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Brush Width	Capacity	Weight	Dimensions (WxLxH)
TT1535G	400W	1000W	220-240V 50Hz	1000rpm	42m	350mm	15L	38kg	480x750x740mm



Overfill cut-off system

- Compact Yet exceptionally manoeuvrable.
- Multi-directional Twin water pick-up nozzles for all round cleaning.
- Cylinder Power Brush Ensures deep cleaning.
- Swing Steering Provides easy directional control.
- Transit Wheels
   Oversized transit wheels allow easy movement to and from any location.
- Simple Control Easy to use operator controls.



Adjustable water flow

Operator controls



# **TwinTec** The Compact Single Disc

The TwinTec 1840 cable machine has been designed to address the question of size being exceptionally compact, yet with performance equal to bigger machines.

The compact design really does allow this machine to clean in areas normally cleaned by hand, yet 30% to 40% faster and better.

Although designed for small and congested areas the TT1840G is equally at home in larger areas and can be used in conjunction with our cable roll, "the cable reel that rolls", extending the cable length from 20m to 40m without any loss of performance.

The style and proportion of the polyform water tanks allow for the machine to adopt a convenient tilt position with only approximately 5 litres in the clean water tank to facilitate single handed brush or pad changing.

> 20m Cable ree (optional)



• **Convenient** Fold flat design for easy transport from site to site.

- **Rugged Construction** Tough all steel chassis design.
- Fully Adjustable Handle For the perfect working position.
- Low Noise Quieter, unobtrusive design means true versatility.
- Easy Change Easy one handed brush or pad changing.

|т



Please note: Available January 2017

Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Pad / Brush Width	Capacity	Weight	Dimensions (WxLxH)
TT1840G	400W	300W	220-240V 50Hz	150rpm	42m	360 / 400mm	18L	40kg	520x880x1132mm

10 (See pages 30-31 for full accessories)







Simple controls



Easy and generous fill cap

## TwinTec A Range of Two

The TwinTec mains cable range has masterful performance moving under its own brush power with amazing speed and purpose. Available with 45 or 55cm scrub width.

When selecting a scrubber dryer machine, the area that needs to be cleaned and the time available to clean it will determine the preferred size of the brush system.

Care must be taken, however, to ensure that bigger is better but not too big, taking into account the obstructions that must be navigated during the daily cleaning cycle.

- TwinFlo Vacuum Motor Provides exceptional wet pick-up.
- Structofoam Tilting Brush Deck Making brush changes quick and simple
- Planetary Gearbox Longlife, oil filled, low load gearbox.
- Simple Control Simple on / off trigger controls.
- Polyform Tanks Heavy duty clean and dirty water tanks.
- Flexifill System Easy filling and emptying system.
- Structofoam Chassis Incredibly tough and chemical resistant Stuctofoam moulded chassis TT4055G

Additional fill and filter point



Fully adjustable handle

Simple controls

Model	Brush Motor	Vac Motor	Power	Brush Speed	Range	Pad / Brush Width	Capacity	Weight	Dimensions (WxLxH)
TT4045G		100014	220-240V	450		400 / 450mm	401	67kg	470x890x1100mm
TT4055G	1500W	1200W	50Hz	150rpm	42m	500 / 550mm	40L	68kg	560x935x1100mm



Tilting deck for easy brush change and storage

NUMETO

TT4045G

Numatio


Full moulded chassis and non-marking wheels

Please note: Available January 2017

# TwinTec Big & Bold

### The TT6650G cable machine is a genuine workhorse providing a truly cost effective answer to big area low cost floor maintenance.

First and foremost the user will find the TT6650G as easy to use as our smaller machines with the control and operation systems to exactly the same specification, it handles like a dream. Big capacity polyform tanks provide a full 60 litre capacity to match the exceptionally stable 65cm single brush scrubbing head, complemented by an oversized, floating aluminium floor tool.



• Polyform Tanks Heavy duty clean and dirty water tanks.


- Structofoam Tilting Brush Deck Making brush changes quick and simple.
- Fully Adjustable Handle For the perfect working position.
- TwinFlo Vacuum Motor Provides exceptional wet pick-up.
- Stainless Chassis Strong stainless steel chassis.



less steel chassis



Easy tank filling access





TT6650G | 1500W | 1200W

#### Please note: Available January 2017

Power	Brush Speed	Range	Pad / Brush Width	Capacity	Weight	Dimensions (WxLxH)
220-240V 50Hz	150rpm	42m	600 / 650mm	60L	87.6kg	970x1260x1230mm

13 (See page 30-31 for full accessories) 13

# TwinTec Battery Compact

The TwinTec 1840 machine has been designed to address the question of size being exceptionally compact, yet with performance equal to bigger machines.

The compact design really does allow this machine to clean in areas normally cleaned by hand, yet 30% to 40% faster and better.



Simple soft touch controls

WARDER BUILDER AUSTRALIS

Easy and generous fill cap

- Battery Pack Quick change 24V gel battery pack.
- Cable Free Total freedom of 24V battery operation.
- Water Feed System 360° water feed system for uniform liquid delivery to floor.
- Fully Adjustable Handle Flat to upright for perfect position.
- Parabolic Squeegee 270° rotating parabolic squeegee system.
- Quick Change Fast, single handed brush or pad changing.
- Hi / Lo Mode For quieter cleaning when needed.



Please note: Available January 2017

	Brush Motor	Vac Motor	Power	Runtime	Recharge Time	Pad / Brush Width	Capacity	Weight	Brush Speed	Dimensions (W
TTB1840G 4	100W	300W	2x12V (24V 18Ah)	45min	6hr	360 / 400mm	18L	52kg	150rpm	520x850x113

Quick change gel battery pack



advance and tomorrow's new classic.





Simple controls

Model Brush Vac TGB3045 300W 400W

14 (See pages 30-31 for full accessories)

#### Please note: Available January 2017

Power	Working- time	Recharge Time	Pad / Brush Width	Capacity	Weight	Brush Speed	Dimensions (WxLxH)
2x12V 4V 55Ah)	upto 2hr	10hr	400 / 450mm	30L	90kg	100rpm	470x890x1100mm

## TwinTec Battery Setting the Standard

### With these machines every part is designed to combine the best in functionality and reliability.

The TGB4045 is the classic Numatic TwinTec 24V battery model. It started its life with 30 litre capacity, now raised to 40 litre, and is today the most popular model worldwide. The premium specification starts with a steel chassis, structofoam tilting brush deck, polyform tanks, fully sealed gel batteries, built in battery charger, heavy duty TwinFlo wet pick-up vacuum system and heavy duty geared brush drive.

The 4055 is one size up from the 4045 containing all the advanced TwinTec 24V features but with a 20% increased cleaning path.

The 4055T (traction) offers effortless cleaning due to the powerful traction unit. A traction model is essential where inclines such as wheelchair ramps are present.



imple controls

- Fully Sealed Gel Batteries Maintenance-free batteries to ensure the highest standard of operational life.
- Twinflo Vacuum Motor Provides exceptional wet pick-up.
- Structofoam Tilting Brush Deck Making brush and pad changing quick and easy.
- Easy Operation Simple on / off trigger control.
- **On-board Charging** Convenient and easy, just plug and go.





On-board charger



Floor tool lifting / lowering handle



Numatte

 
 Model
 Brush Motor
 Vac Motor

 TGB4045
 300W
 400W

 TGB4055T
 300W
 400W

 T= Traction drive

Additional fill and filter point



#### Please note: Available January 2017

Power	Runtime	Recharge Time	Pad / Brush Width	Capacity	Weight	Traction Drive	Brush Speed	Dimensions (WxLxH)
	0.051		400 / 450mm		128kg			470x1070 x1160mm
2x12V 4V 100Ah)	2.25hr	8hr	500 / 550mm	40L	134kg	-	100rpm	560x1115
-	2.0hr		500 / 550mm		140kg	250W		x1160mm

# **TwinTec** Battery 50% More Capacity for bigger areas

Both models of TGB6055 have 60 litre capacity

and a 55cm (20") single brush scrubbing

### Easy-to-use controls combined with professional cleaning.

The 55cm (20") size of TwinTec is becoming more and more popular and, in support of this, we have introduced two new models with 60 litre capacity, a 50% increase over the 40 litre models and available in both traction and non-traction specifications.



Plug-in charger syste



Simple to use control panel TGB6055 shown

- Key Ignition Switch
- Hours meter
- Battery level indicator
- Vacuum On / Off
- Water flow On / Off



### ...50% More Capacity for bigger areas





- Simple Operator Controls 2 switches for vacuum and water.
- **On-board Charging** Convenient and easy, just plug and go.
- Gel Batteries Up to 2.25hr runtime, 8hr charge time.
- Flexifill System Easy filling and emptying with flexifill system.
- Battery and Hour Meter Simple clear hour / battery indicator.
- Traction Drive System Makes the cleaning of inclines safer and easier (TGB6055T).

TGB6055 TGB60551 T= Traction drive

path, dual brush pressure selection, built in battery charging, easy fill and easy emptying facilities, with added traction power drive for the 6055T model which would be essential if inclines or ramps are involved.

Power	Runtime	Recharge Time	Pad / Brush Width	Capacity	Weight	Drive Speed	Brush Speed	Dimensions WxLxH
2x12V	2.25hr	0hr	500 /	60L	165kg	-	100rpm	560x1280 x1160mm
2x12V V 100Ah)		8hr	550mm			4.2kph		

## Twintec Vario Two Into One Goes Again, Even Bigger

The TwinTec Vario 5565 represents, in every way, the optimum walk behind traction auto-scrubber with a range of advanced, yet practical, features that truly allow us to claim... "Best in Class".

This TwinTec gets its Vario name from the fact that this one machine can, by a no tools adjustment and simple brush change, be set to operate at either a 55cm or 65cm scrubbing width... two machine choices in one.



#### In the 65cm mode the scrubbing head is automatically expanded to a practical offset operating mode, providing a 100mm head extension to the right hand side. This simple arrangement allows improved edge cleaning especially in aisles with racking or other obstructions.

The operator controls are a separate feature in their own right with independent selection of speed, water flow and chemical dosing all built in to the basic unit, all of which can be set to provide total convenience and consistency of operation.




- Flexifill System Easy filling and emptying with the flexifill system.
- Complete Cleaning Control Simple one touch dosing control and versatile variable speed control.
- Adjustable Scrub Widths 55cm or 65cm scrubbing width by virtue of the adjustable dual setting Vario deck design.
- **Spot Cleaning** Heavy duty spot cleaning means operator can over-ride standard brush pressure to 50kg for extra performance.
- Easy Transportation Built in easy transit mode for easy transportation between areas.

### • On-board Charging Convenient and easy, just plug and go. Fully sealed low maintenance gel batteries.

- Simple Operator Control Nutronic soft touch operator controls.
- Safety Features Built in emergency stop button and removable power off key are just two of the many safety features.

#### The unique TwinTec 55cm / 65cm dual brush system...

A simple, no tool adjustment and brush change allows a selection of either 55cm or 65cm scrubbing widths.



Model	Brush Motor	Vac Motor
TTV5565	2x330W	600W
Brush Speed	Water Capacity	Nuch Capa

TTV5565

Simple to use Nutronic control par

Easy battery

Beneath the hinged dirty water tank sits the operating heart of the Vario with its 200Ah gel battery and charging system, high performance suction unit and NuChem dosing facility... all easily accessible.

# **Compact** Ride-0n 8055

### Not too big, not too small, good capacity, simple controls, excellent performance and very competitive in terms of price.

In truth the CRO8055G is competitive with most walk behinds of the same size. So now you can sit rather than walk and by virtue of the exceptional manoeuvrability, substantial time will be saved on middle size applications.

The CRO8055G also introduces the logic of two machines in place of something much bigger or, to put it another way, Two for the Price of One with added versatility and convenience.

The CRO will go into places where bigger machines are not suitable and anything smaller is just too small.

- Compact Design Means easy cleaning in tight spaces.
- Anti-tip System Prevents the machine from tipping when cornering on full lock.
- On-board Charging Easy and convenient, just plug and go. Fully sealed low maintenance Gel batteries.
- Flexifill System Easy filling and emptying with the flexifill system.
- Easy Operator Control With fully adjustable speed control.
- Safety Features rgency stop button, removable er off key, horn button and built in hazard warning light are just a few of the safety features included.
- Easy Maintenance Easy access to batteries and fuses





Heavy duty integral chassis (CRO8055G shown)

Model	Brush Diameter	Capacity	Battery Power	Runtime	Recharge Time	Traction Drive	Clean Speed	Vacuum Motor	Brush Speed	Brush Motor	Dimensions (WxLxH)
CRO8055G / 100 CRO8055G / 200		80L	2 x 12V (24V) = 100 Ah 2 x 12V (24V) = 120 Ah		2 x 100 Ah = 10A - 8hr 2 x 120 Ah = 20A - 7hr	400W	6km/h max	400W	150rpm	1 x 600W	805x1460x1160mm
CR08072G	2 x 370mm	80L	2 x 12V (24V) = 120 Ah 2 x 12V (24V) = 100 Ah		2 x 100 Ah = 10A - 8hr 2 x 120 Ah = 20A - 7hr	400W	6km/h max	400W	150rpm	1 x 600W	805x1460x1160mm

22 (See pages 30-31 for full accessories)

## Compact Ride-ON Twin Brush 8072





Anti-tip side buffers



Charger port

#### CRO8072G twir





## TwinTec Ride-ON & Serious Workhorse

Easy brush access

TRO650G

ining Spe

3.5km/h

s (WxLxH)

944x1676x1425mm

)rive Spee

0-7.0km/h

600W

365ka

8hr

imbing Grad

11%

A more user friendly ride-on scrubber dryer would be hard to find. Designed to provide long, simple and reliable service day in day out whatever the environment.

The TRO650G is based on the well established engineering of the Vario TTV678 model but simplified to provide a truly professional, cost effective workhorse. You can vary the water flow and the operating speed to suit a whole host of conditions from big areas lightly soiled to heavy duty scrubbing in more arduous conditions.



The TRO650G is blessed with a commanding operator driving position, front wheel traction drive, a magnificent turning circle and one pass performance that really will ensure you get the standard you want, exactly when you want it ... and fast.

### ...A Serious Two Brush Workhorse

- Twin Brush 650 twin brush power head cleaning system.
- Easy Brush Access Easy side access to brushes for maintenance.
- Controlled Cleaning Fully adjustable water flow rate.
- **On-board Charging** Easy and convenient, just plug and go. Fully sealed low maintenance Gel batteries.
- Simple Operator Control Full dashboard control with soft touch Nutronic controls.
- Safety Features Emergency stop button, power off removable key, horn button and hazard warning light and built in reversing alarm are just a few of the many safety features included.
- Easy Maintenance Easy access to batteries and fuses for maintenance.



Full control dashboa







TRO Aluminium / Polyurethane floor tool



24 (See pages 30-31 for full accessories)

TRO650G 2 x 400W 600W 4 x 12V (24V) = 200Ah 3.5hr

Water Canacit

120L

Powe

Water Flow Rate

3. 2. 1. 0.5L/min

Model

Scrub Width

650mm

Brush Motor

Brush Speed

200rpm





Drive wheel protector

A full 120 litre capacity with a fixed 650mm twin brush power head the TRO650G is ready to go.



# **TwinTec** Vario Three Into One Does Go

A comfortable, driver friendly, 120 litre, front wheel drive machine with a fantastic turning radius, gets in and out of places other machines just won't go.

The TwinTec Vario "three in one" (3 in 1) design has proved itself to be almost the perfect balance between sound common sense engineering and innovative and truly functional technology.

Yes, one machine which can be set to 3 different working widths: 650, 750 and 850 and all at the flick of a simple selection lever. This doesn't even need tools - anybody can do it at any time. You want it wide - fine ... you want it narrow - 30 seconds is all that it takes.

### The Vario TTV678G, three brush widths in one system

The unique arrangement of 3 independent scrubbing heads which, by virtue of a simple adjustment mechanism, can provide a choice of scrubbing widths which, with the addition of a selection of brushes and pads, can provide customised performance on almost any surface application.







### As unique today as when it started - patented technology

- Vario 3 in 1 Brush System Simple adjustment mechanism provides a choice of scrubbing widths suitable for almost any surface.
- Easy Dosing Pre-sets Correct chemical dosing for every task.
- Complete Cleaning Control Operator has full control of cleaning speed, brush speed, water flow and chemical dosing.
- Simple Operator Control Soft touch dashboard control system.
- Easy Maintenance Easy access to batteries and fuses for service purposes and brush change is simple with the swing out brush cover.
- On-board Charger Simple and convenient, just plug and go. Fully sealed low maintenance Gel batteries.
- Small Turning Radius Means great cleaning even in tight spaces.
- Safety Features Emergency stop button, power off removable key, horn button and hazard warning light and built in reversing alarm are just a few of the many safety features included.
- Easy Maintenance Easy access to batteries and fuses for maintenance.









Dosing controls											
	Model	Brush Motor	Vac Moto								
	TTV678G	3x24V 400W	24\ 600\								
	Scrub Widths	Brush Speed		ا Ca							
	650mm 750mm 850mm	50 / 10 150 / 200									



#### Vario, the machine that gives you what you want.

In many applications changing circumstances change specific needs, so with the Vario you can change the specification to suit your exact requirements. It's not only the working widths that can be changed; it's the full operating performance that is under the driver's complete control - cleaning speed, brush speed, water flow and chemical dosing, nothing left to chance.



Easy brush change

	Power	Runtime	Recharge Time	Traction Drive	Drive Speed	Cleaning Speed	Climbing Gradient			
	V (24V) = 300A V (24V) = 400A (Optional)		8-12hr	600W	7.0km/h	3.5km/h	11%			
Vater pacity	Nuchem Capacity	Water Flow Rate	Nuchem Mix	Gross W	eight (full)	Dimensions (WxLxH)				
20L	Optional 5L	4L/min 3L/min 2L/min 1L/min	25:1 50:1 75:1 100:1		+620kg +684kg	1054x1676x1425mm				

## Brushes and Pad Drive

Careful selection of quality brushes and pads will ensure your Floorcare machine always operates at its best.



Polyscrub Brush General scrubbing duties suitable for most floor types.

Longlife Light Scrubbing Brush

Can provide extended cleaning life in

brushes. Suitable for light scrubbing

and polishing.

9

comparison to alternative light scrubbing

Flexi PadLoc Drive Board For 300rpm Machines

Elexi specification provides optimum stability

needed for 300rpm speed machines.

Flexi NuLoc2 Drive Board

5



Nyloscrub / Shampoo Brush Suitable for when lighter scrubbing is required. Can be used for shampoo cleaning.

Nyloscrub Cylinder / Longlife Cylinder Brush

Replacement cylinder brushes for TT1535G

High Speed Spider PadLoc Drive Board

Spider design specification provides optimum

stability needed for 450rpm speed machines.

available in two material specifications.

6

10

14

Porcupine Pad Holder

when required.



Union Mix Polish Brush Ideal for polishing uses a well-proven mix of high quality bristles for optimum results.

Longlife Heavy Duty Scrubbing / Stripping Brush

comparison to alternative heavy duty scrubbing

Alternative to PadLoc that may be required when

using a rotary machine in certain circumstances.

brushes. Suitable for heavy duty scrubbing.

Can provide extended cleaning life in

7

5

15

Nuplex Pad

NuLoc2 Drive Board

Suitable for general use.



Longlife Scrubbing Brush Can provide extended cleaning life in comparison to standard scrubbing brushes. Suitable for general scrubbing.



PadLoc Drive Board A simple, effective and easy to use system. Pads are located securely and perfectly centred every time. Suitable for general use.



High Speed Spider NuLoc2 Drive Board Spider design specification provides optimum stability needed for 450rpm speed machines. NuLoc2 offers an alternative to PadLoc.



NuShine Topline Speed Burnish Pad Burnishing pad for use with NuShine HNS1550 (500mm). Supplied as pack of 5.





Flexi specification provides optimum stability

needed for 300rpm speed machines.

NuLoc2 offers an alternative to PadLoc.

Wire Scarifying Brush Suitable for scarifying a range of floor surfaces, typically used in preparation of concrete flooring.



Can be used as an alternative pad drive board

Sandotex Disc Drive Highly abrasive disc for use on rotary machine.



Low water, chemical free maintenance suitable

for a wide range of applications.

Carbotex Grinding Disc Carbon based discs provide high abrasive properties with long life.



Heavy Duty Scarifying Disc - Spirotex 6 Head Heavy duty scarifying board fitted with 6 wire Spirotex heads.

					Rotary Floor Cleaners					Twin	Vario / Ride-on										
Type	Image No.	Description	Brush / Pad Size mm	Part Number	HFM1 015 / HFM1 515 / 1523 / NR1500S	HFM1 530	HFM1 545	HFT1 530	HNS1550	NLL332	TT1 535G	TT1840G / TTB1840G	TGB3045 / TT4045G TGB4045	TT4055G / TGB4055T	TGB6055 / TGB6055T	TT6650G	TTV5565G	CR08055G	CR08072G	TRO650G	TTV678G
			330 370	606033 903449						•									•x2		
	1	Polyscrub Brush	400 450	606105 606203	•			•				•									
			450 550	606028	•			•					•	•	•			•			
			650 330	606021 606556						•						•					
		2 Nyloscrub Brush	370	903994						•									•		
	2		450 550	606204	•			•					•	•	•						
			650	606550 606554								-	-	•	•	•		•			
		Listen Mix Delick Devich	330	606104						•											
	3	Union Mix Polish Brush	400 450	606102 606202	•	•	•	•				•									
			370 450	606302 606306	•			•				•	•						•		
	4	Longlife Brush	450 550	606551	•			•					-	•	•			•			
es			650	606555 606173												•					
Brushes	1	Octo Polyscrub Brush	280 300	606173													•				•
•		-	330	606174													•			٠	
	2	Octo Nyloscrub Brush	280 300	606171 606151													•				•x3
			330	606172													•			•x2	
	2	Octo High Density Nyloscrub Brush	330 280	606253 606175								-					•x2			•	
	4	Octo Longlife Brush (green)	300	606153																	•
			330 280	606176 606326								-					•			•	
	5	Octo Longlife Brush (red)	300	606327																	•
			330 370	606328 606303								•					•		•	•	
	5	Longlife Light Scrubbing Brush (red)	450	606307	•			•					•								
	N/A	Longlife High Lustre Polishing Brush (blue) (HFM / NR)	550 450	901050 606308	•	•		•						•	•						
	6	1535 Nyloscrub Cylinder Brush	400	606225	-						•										
	6 7	1535 Floortec Cylinder Brush Floortec Scrubbing / Stripping Brush (black)	450	606226 606305	•			•			•										
	1				-			•										I			
			360 400	606400 606401	•			•				•	•					-	•		
	8	PadLoc Drive Board (black)	500	606403										•	•			•			
PadLoc			600 280	606404 606405												•	•				
Pa	8	Octo PadLoc Drive Board	300	606406																	•
	9	Flexi PadLoc Drive Board for 300 rpm	330 400	606407 606411		•		•			_	+					•			•	
	10	High Speed Spider PadLoc Drive Board for 450 rpm	400	606412			•														
			360	900524								•							•		
	11	NuLoc2 Drive Board	400	900525 900526	•								•	•	•			•			
N			600	900717												•					
NuLoc2	11	Octo NuLoc2 Drive Board	280 300	900718 900719													•				•
ž			330	900720													•			•	
	N/A 12	NLL Pad Drive NuLoc2 Drive Board (HFM / NR)	330 400	606111 900527	•		•			•											
	13	Flexi NuLoc2 Drive Board for 300rpm (HFM / NR)	400	900528		•		•													
ed	17	Wire Scarifying Brush	400	606207	•																
Specialised	18 19	Sandotex Disc Drive	400	606209	•																
Sped	19 20	Carbotex Grinding Disc Heavy Duty Scarifying Disc Spirotex 6-head	400 400	606208 606211	•																
			350	900967								•									
×	15	NuPlex Pads Starter Pack	430	900969	•	•	•	•					•								
Nuplex			500 350	900971 900975								•		•	•			•			
z	15	NuPlex Pads Pack of 5	430	900974	•	•	•	•					•								
			500	900973										•	•			•			
Other	14 16	Porcupine Pad Holder NuShine Topline Speed Burnish Pad	400	606700 901622	•			•													
0			000	JUIDEL									1								
auida	ance o	only - Each application should be assessed before selec	tion of F	orush / nad	C	oplied v	with at-	andord	maak	ino											
					JUC	N DOING	VILLI SLO	niudiu	maull	10											

ach application should be assessed before selection of brush / pad. Specification subject to change without prior notice.

28

# Accessories

#### Using genuine Numatic accessories will ensure you achieve the best results from your FloorCare machine.

Each accessory is developed with professional cleaners in mind, good quality design makes all the difference when a task is repeated day after day.

### Hurricane and NuSpeed Accessories



HFT / HFM Solution Tank PN:606890





NR Solution Tank PN:606084





NLL Solution Tank PN:606101



NR 10kg Weight For NR 1500S PN:606113 HFM 10kg Weight For HFM 1500S PN:606077



Dustrol Kit (Blue) PN:900834 NR Dustrol Kit (Grey) PN:606056

HFM / NR Dustrol Control Brush Ring (Also Standard With Dustrol Kits) PN:606079

### TwinTec / Vario Blade Sets





Optional Replacement Polyurethane Blade Set (4 pieces) PN:606091









NR Optional Spraytec Kit PN:606054 HFM / HNS Optional Spraytec Kit PN:606325







### TwinTec / Vario Accessories





All TT / TGB Machines Wander Floor Kit (32mm) (Except TT / TTB1840G) PN:607250

All TGB / TRO / TTV Machines Wander Floor Kit (38mm), TGB PN:606193, TRO / TTV PN:606182 (Except TT / TTB1840G)





Emptying Hose Extension Kit PN:609100

TTV678G 38mm Emptying Hose Extension PN:606186





CRO Spray Mop Mounting Kit PN:903182

TRO / TTV / CRO Caddy Kit (Red) CRO PN:902505 (shown ab TRO / TTV PN:902739





20m Cable Roll Extension UK PN:612002 20m Cable Roll Extension EUR PN:612003

NuTab dosing tablets 90 x 20 Litre Bucket 9 x packs of 10 Tablets PN:903981



CRO Machines Wander Floor Kit (38mm), c/w fitting kit PN:903183



TTV678G Battery LED Front Light Kit PN:606170



TRO / TTV Replacement Seat Cover PN:604053



TTB1840G Battery & Charger Pack UK PN:606266 EUR PN:606267 CH PN:606268 USA PN:606269 SA PN:606270 AUS PN:606271

TTB1840G Charger Pack UK PN:606272 EUR PN:606273 CH PN:606274 USA PN:606275 SA PN:606276 AUS PN:606277 (Boxed) PN:606260



TwinTec / Vario Aluminium Floor Tool Wide Angle Adjustable Castor Plate Upgrade Kit PN:606319




#### Numatic International Limited,

Chard, Somerset, TA20 2GB, UNITED KINGDOM

Tel: 01460 68600 Fax: 01460 68458

www.numatic.co.uk



13/17 rue du Valengelier, EAE la Tuilerie, 77500 Chelles, FRANCE

Tel: 01 64 72 61 61 Fax: 01 64 72 61 62

www.numatic.fr



#### Numatic International

BeNeLux Distribution Numatic International BV Postbus 101 2400 AC Alphen aan den Rijn NEDERLAND

Tel: 0172 467 999 Fax: 0172 467 970

#### www.numatic.nl



#### Numatic International GMBH

Fränkische Straße 15-19, 30455 Hannover DEUTSCHLAND

Tel: 05 11 98 42 16 0 Fax: 05 11 98 42 16 20

#### www.numatic.de



#### Numatic International Schweiz AG.

Sihlbruggstraße 142 6340 Baar, SCHWEIZ

Tel: 041 768 07 60 Fax: 041 768 07 69

www.numatic.ch



### Numatic International

Centro de Negócios da Maia Rua Albino José Domingues n.º 581 4470 - 034 Maia PORTUGAL

Tel: 351 220 047 700

#### www.numatic.pt



Numatic International (Pty.) Ltd.

16th & Pharmaceutical Roads, Midrand, Gauteng, S.A. 1685.

Tel: 0861 686 284 Fax: 0861 686 329

www.numatic.co.za



Specification subject to change without prior notice. 901450/1116 ©Numatic International Limited 2017