## SteamForce SF6



## A small unit that packs a big punch!

## Introducing the new **OSPREYFRANK** range

- Compact but tough with robust stainless steel body
- Industrial quality steam socket
- Professional boiler with continuous boiler refill
- Twin external detergent facility for ease of change
- Steam volume regulator
- Front locking castors
- Simple and clear operation
- Cost effective
- Environmentally friendly
- Ideal for small/medium manufacturing/ engineering facilities



## +44 (0) 1242 513123 www.ospreydc.com

Machine Ordering Code: M6057

SF6 Machine Specification				
Power Supply	400 Volt 50Hz 16 Amp - 5 Pin only	Cable Length	5 metres	
Maximum Power	5,500 Watt	Machine Dimensions (W x D x H) cm	50 x 82.5 x 100	
Steam Pressure	10 Bar	Net Weight	32Kg	
Boiler Capacity / Boiler Material	3.6 Litres / RVS AISI 304	Shipping Weight	39Kg	
Detergent Capacity	2 x 5 Litre	Certification/Marking	CE, IPX4	
Heating Up Time	Approx. 6 minutes	Max. Boiler Temperature	185°C	
Steam production	150 gr./min	Adjustable Output Regulator	Yes	
Autonomy	Continuous Operation	Indicator for Lack of Water	Yes	

Flexible 3m Hose A03059	Industrial Lance 400mm Hooked Nozzle <b>A03125</b>
Industrial Lance 900mm hooked nozzle <b>A03130</b>	Industrial Squeegee 350mm <b>A03133</b>
Nylon Detail Brush <b>A03134</b>	Copper Detail Brush A03136
Stainless Steel Detail Brush <b>A03139</b>	50mm Round Nylon Brush <b>A03140</b>
50mm Round Copper Brush <b>A03141</b>	50mm Round Stainless Steel Brush <b>A03143</b>
50mm Scotch brite round pad <b>A03145</b>	



Unit 41, Central Way, Cheltenham Trade Park, Cheltenham, GL51 8LX T: +44 (0) 1242 513 123 F: +44 (0) 1242 518 666 E: info@ospreydc.com W: www.ospreydc.com

© 2012 OspreyDeepclean Ltd