SteamForce SF Eco



The little machine with the big steam

Introducing the new **OSPREYFRANK** range

- Compact but tough with robust stainless steel body
- Industrial quality steam socket
- Professional with continuous boiler refill
- External detergent facility for ease of change
- Steam volume regulator
- Front locking castors
- Simple and clear operation
- Cost effective and environmentally friendly
- Ideal for small areas with no vacuum requirement
- Also available in 120v version

Machine Ordering Codes 230v: M6054 120v: M6053



+44 (0) 1242 513123 www.ospreydc.com

SF Eco Machine Specification				
Power Supply	230v 50Hz 13Amp / 120v 60Hz 14Amp	Cable Length	4 metres	
Maximum Power	3,000 Watt 1,700 Watt	Machine Dimensions (W x D x H) cm	37cmx82.5cmx100cm	
Steam Pressure	6 Bar nominal	Net Weight	25Kg	
Boiler Capacity / Material	2.3 Litres / RVS AISI 304	Shipping Weight	32Кg	
Detergent Capacity	2 x 5 Litre	Certification/Marking	CE, IPX4	
Heating Up Time	Approx. 5 minutes	Max. Boiler Temperature	160°C	
Steam production	60 gr./min	Adjustable Output Regulator	Yes	
Autonomy	Continuous Operation	Indicator for Lack of Water	Yes	

SF Eco Standard Steam Only Accessories				
Õ	Steam only Hose 2.5m A03056		Extension Tubes A03060	
9	Floor Tool A03061	Image to follow	Brush Adaptor for floor tool A03062	
	Cover for Floor Tool A03071		Large Triangular Brush A03072	
1	Squeegee Tool 24cm A03063		Short curved nozzle A03069	
	Long nozzle A03065		Nylon Detail Brush A03081	
۷	Copper Detail Brush A03082		Stainless Steel Detail Brush A03083	
6	50mm Round Nylon Brush A03074		Cotton Cloth A03028	
Unit 41. Central Way. Cheltenham Trade Park. Cheltenham. GL51 8LX				

Unit 41, Central Way, Cheltenham Trade Park, Cheltenham, GL51 8LX T: +44 (0) 1242 513 123 F: +44 (0) 1242 518 666 E: info@ospreydc.com W: www.ospreydc.com

© 2012 OspreyDeepclean Ltd

OSPREYDEEPCLEAN